





STRAPPING - 100' PER BOX				:	UCKLE	S	
WIDTH	THICK- NESS	MATERIAL	PART NO.	PRICE	PART NO.	BOX QTY	PRICE
3/8"	.025	Stainless	SS-375	\$72.80	CS-375	100	\$56.06
1/2"	.031	Stainless	SS-500	99.53	CS-500	100	66.98
5/8"	.031	Stainless	SS-625	141.07	CS-625	100	83.82
3/4"	.031	Stainless	SS-750	169.62	CS-750	100	120.12
3/8"	.025	Galvanized	SG-375	37.86	CG-375	100	28.39
1/2"	.031	Galvanized	SG-500	45.86	CG-500	100	34.32
5/8"	.031	Galvanized	SG-625	55.33	CG-625	100	40.77
3/4"	.031	Galvanized	SG-750	65.52	CG-750	50	27.30

## **Banding Tools**

<b>BANDING TOOLS</b>				
PART No.	DESCRIPTION	PRICE		
C-2 CT	Crimping Tool. Lightweight side-entry jack type	\$279.62		
F-38 CT	Locking Tool. Portable hand tool used to apply punch type 3/8" and 5/8" band clamps	53.84		
F-40 CT	Hand Tool. Intermediate hand tool for 3/8" and 5/8" band clamps	93.74		
F-175 CT	Hand Held Tool. Application of 3/4" K clamps	538.58		

Worm Gear Hose Clamps
Combination Hexagon and Screwdriver Slotted
Screw. SAE 300 series stainless band and
housing with SAE 1018 case-hardened steel,
zinc plated and chromate dip screw.



K-Series Band Clamps
The Universal Preformed Clamp. Can be center punched or rolled over. Stainless steel clamp bands are 300 series stainless steel, buckles are

302 series stainless steel.



WORM GEAR HOSE CLAMPS 5/16"" Band Width with 1/4" Hex Head						
DIA. RANGE BART NO BRICE						
FROM	ТО	PART NO.	PRICE			
7/32"	7/32" 5/8"		\$1.05			
7/16" 25/32"		MH-6	1.05			
1/2"	1.23					
<b>9/16</b> " <b>1-1/16</b> " <b>MH-10 1.23</b>						
Maximum Recommended Torque 10 in. lbs.						

1/2" Band Width with 5/16" Hex Head					
11/16"	1-1/4"	HS-12	1.41		
13/16"	1-1/2"	HS-16	1.41		
13/16"	1-3/4"	HS-20	1.41		
1-1/16"	2"	HS-24	1.41		
1-5/16"	2-1/4"	HS-28	1.46		
1-13/16"	2-3/4"	HS-36	1.50		
2-1/16"	3"	HS-40	1.82		
2-5/16"	3-1/4"	HS-44	2.00		
2-9/16"	3-1/2"	HS-48	2.00		
2-13/16"	3-3/4"	HS-52	2.18		
3-1/16"	4"	HS-56	2.18		
3-5/16"	4-1/4"	HS-60	2.27		
3-9/16"	4-1/2"	HS-64	2.27		
1-7/8"	5"	HS-72	2.46		
3-1/8"	6"	HS-88	2.91		
4-1/8"	7"	HS-104	3.00		
Maximum Recommended Torque 30 in. lbs.					

Maximum Recommended Torque 30 in. lbs.						
9/16" Band Width with 5/16" Hex Head						
<b>7-1/8</b> " <b>10</b> " HS-152 <b>4.76</b>						
9-3/8" 12-1/4" HS-188 5.23						
<b>17-1/8" 20"</b> HS-312 <b>8.28</b>						
Maximum Recommended Torque 30 in. lbs.						

K-SERIES BAND CLAMPS Galvanized					
I.D. SIZE	WIDTH	THICK- NESS	PART NO.	PRICE	
1-13/16"	3/8"	.025	K-3	\$1.09	
1-3/8"	3/8"	.025	K-311	1.15	
1"	5/8"	.031	K-4	1.53	
1-1/4"	5/8"	.031	K-5	1.58	
1-1/2"	5/8"	.031	K-6	1.69	
2"	5/8"	.031	K-8	1.80	
2-1/2"	5/8"	.031	K-10	1.97	
3"	5/8"	.031	K-12	2.18	
4"	5/8"	.031	K-16	2.62	
6"	5/8"	.031	K-24	3.39	

K-SERIES BAND CLAMPS Stainless Steel							
I.D. SIZE	I.D. SIZE WIDTH THICK-NESS PART NO. PRICE						
1-13/16"	3/8"	.025	KS-3	\$1.69			
1-3/8"	3/8"	.025	KS-311	1.91			
1"	5/8"	.031	KS-4	2.89			
1-1/2"	5/8"	.031	KS-6	3.17			
2-1/2"	5/8"	.031	KS-10	4.15			

21

KH METALS AND SUPPLY 2727 Main St. Riverside, CA 92501