

Cable Pullers - Pow'R-Pulls

- Galvanized, Aircraft Quality Cable
- Precision-cast Aluminum Alloy Ratchet Wheel
- Heavy Gauge Steel, Reinforced Ratchet Guard
- Drop-Forged Steel Slip Hooks with OSHA Recommended Safety Latches
- Interlocking, Precision Fit, Steel Alloy Pawls with Safety Spacer Sleeve
- Cold Rolled, High Strength, Tempered Steel Frame and Handle
- Aircraft-type, Heat Treated Bolts
- High Tensile, Fully Rotating Steel Swivel
- Trouble Free, "Notch-At-A-Time" Letdown
- Permanent, Comfortable, Non-Slip Grip



MAASDAM

RATED CAPACITY	MAX REACH	ITEM #	PRICE EACH
1 Ton	12'	144-S-6	\$48.50
2 Ton	6'	144-SB-6	48.50
12' Replacement Cable		9700BX	15.99

Heavy Duty Industrial Hydraulic Jacks

- Tested to 150% of rated capacities
- Not affected by temperature extremes
- Low profile truck models or standard models
- Rigidly adheres to ANSI and JIS standards
- Pump handle included with all models
- Electrically welded base and cylinders to assure strength and eliminate leaks
- Common release valve assemblies and other interchangeable parts for quick repair are standard
- All models work in upright, angle or horizontal position
- Carrying handle on 12-1/2 - 100 ton models



JET

RATED CAPACITY	CLOSED HEIGHT	MAX HEIGHT	NET WEIGHT	ITEM #	PRICE EACH
2 Ton	7-1/8"	13-5/8"	4 lbs.	453301	\$59.22
3 Ton	7-1/2"	14-3/8"	5 lbs.	453303	72.38
5 Ton	7-7/8"	15-1/2"	8 lbs.	453305	98.70
8 Ton	7-7/8"	15-1/2"	12 lbs.	453308	111.86
12 Ton	9-1/2"	18-1/2"	17 lbs.	453312	164.50
17 Ton	10-3/8"	20"	23 lbs.	453317	223.72
22 Ton	10-5/8"	16-7/8"	27 lbs.	453322	230.30
22 Ton	7-1/8"	12"	22 lbs.	453323K	216.20

NOTE: When used at an angle or in the horizontal position, pump must be in upright position and piston movement is reduced

Snatch Blocks

- Drop Side with Swivel Hook
- Bronze bushed with pressure grease fitting



RATED CAPACITY	SIZE & STYLE	WIRE ROPE DIA.	NET WEIGHT	ITEM #	PRICE EACH
2 Ton	3" Single	3/8"	5 lbs.	BLK3HK	\$33.40
4 Ton	4-1/2" Single	1/2"	12 lbs.	BLK4-1/2HK	60.88
8 Ton	6" Single	3/4"	27 lbs.	BLK6HK	99.00

Push / Pull Trolley

- Use on straight or curved track
- Built-in bumper guard
- Can be used with H and I-Beams
- Wheels are equipped with lifetime lubricated ball bearings
- Adjustable to fit various sizes of flange and I-beams
- Can be installed or removed at any point along the track



RATED CAPACITY	BEAM FLANGE WIDTH	NET WEIGHT	ITEM #	PRICE EACH
1.0 Ton	3" - 6"	23 lbs.	PT-100	\$151.30
2.0 Ton	4" - 7"	37 lbs.	PT-200	189.38
3.0 Ton	4" - 7-3/4"	57 lbs.	PT-300	352.70