

Flap Disc

ZIRCONIUM OXIDE FORTE - Type ZF

Suited for universal use at maximum stock removal rates, e.g. finishing of welds on surfaces. Also for light deburring and beveling work on stainless and high-temperature steels.



| ZIRCONIUM OXIDE FORTE | | | | | |
|-----------------------|-----------|------|---------|----------|---------|
| SIZE DIA. | BORE DIA. | GRIT | MAX RPM | ITEM NO. | PRICE |
| 4" | 5/8" | 40 | 15,300 | 60890 | \$12.84 |
| | | 60 | | 60891 | 12.84 |
| | | 80 | | 60892 | 12.84 |
| 4-1/2" | 7/8" | 40 | 13,300 | 60895 | 14.46 |
| | | 60 | | 60897 | 14.46 |
| | | 80 | | 60898 | 14.46 |
| | 5/8"-11 | 60 | 60927 | 15.62 | |
| 5" | 7/8" | 40 | 12,200 | 60902 | 16.12 |
| | | 60 | | 60904 | 16.12 |
| | | 80 | | 60905 | 16.12 |
| 7" | 5/8"-11 | 40 | 8,500 | 60946 | 27.23 |
| | | 60 | | 60948 | 27.23 |
| | | 80 | | 60949 | 27.23 |

Sanding Belts

ALUMINUM OXIDE - Type A

Recommended for universal use on all materials, e.g. on alloyed and unalloyed steels, structural steel, tool steel, high speed steel, corrosion and acid resistant steels, non-ferrous metals such as aluminum, brass etc., plastics and woods.



| ALUMINUM OXIDE | | | | |
|----------------|----------------|------|----------|---------|
| WIDTH | OVERALL LENGTH | GRIT | ITEM NO. | PRICE |
| 6" | 48" | 60 | 49467 | \$15.66 |
| | | 80 | 49468 | 15.66 |

Shop Rolls

Shop rolls are used in workshops, maintenance, tool-making, fabrication shops and production applications. The material can be torn to any length for practicality and economy.



| SHOP ROLLS | | | | | |
|----------------|------------|--------|------|----------|---------|
| TYPE | SIZE WIDTH | LENGTH | GRIT | ITEM NO. | PRICE |
| ALUMINUM OXIDE | 1" | 50 yd | 80 | 47103 | \$32.38 |
| | | | 120 | 47105 | 32.38 |
| | | | 180 | 47107 | 32.38 |
| | | | 240 | 47109 | 32.38 |
| | | | 320 | 47111 | 32.38 |
| | 1-1/2" | 50 yd | 80 | 47153 | 46.99 |
| | | | 120 | 47155 | 46.99 |
| | | | 180 | 47157 | 46.99 |
| | | | 240 | 47159 | 46.99 |
| | | | 320 | 47161 | 46.99 |

Flap Wheels - Shaft Mounted

The laminae holding the abrasive grain are arranged like a fan around the shaft of the tools. They adapt themselves readily to irregular surfaces. The abrasive grain is securely bonded with heavy-duty resins. Best results are achieved when run at recommended speed.



Applications:

Fine grinding and polishing work on large irregular surfaces in tool and mold making. Working in smaller and difficult to reach areas in weldment, machine housings, aircraft, etc. Working on fittings of heavy or light metals.

| FLAP WHEEL with 1/4" shank | | | | | |
|----------------------------|------------|------|---------|----------|---------|
| SIZE DIA. | SIZE WIDTH | GRIT | MAX RPM | ITEM NO. | PRICE |
| ALUMINUM OXIDE | | | | | |
| 1" | 1" | 80 | 25,000 | 45185 | \$7.19 |
| 1-5/8" | 1" | 80 | 25,000 | 45233 | 7.08 |
| 2" | 1" | 80 | 25,000 | 45239 | 9.06 |
| 3" | 1" | 80 | 25,000 | 45209 | 12.73 |
| 3" | 2" | 80 | 25,000 | 45215 | 16.75 |
| POLINOX | | | | | |
| 2" | 1-1/4" | 100 | 12,000 | 46220 | \$15.56 |
| 3" | 2" | 100 | 7,500 | 46222 | 26.52 |

Mounted Stones



| MOUNTED STONES with 1/4" SHANKS | | | | | |
|---------------------------------|--------------|---------|------|----------|--------|
| STONE DIA. | STONE LENGTH | MAX RPM | GRIT | ITEM NO. | PRICE |
| 3/4" | 2-1/2" | 19,800 | 30 | 39000 | \$5.40 |
| 1" | 2-3/4" | 16,100 | 30 | | 5.40 |
| 7/8" | 2" | 19,860 | 30 | | 5.40 |
| 1" | 2" | 15,900 | 30 | | 5.40 |
| 2" | 1" | 14,500 | 30 | | 5.40 |