

Cutting Oil

CLEAR - Recommended for hand threading applications. A blend of high quality mineral oils with sulfur base. Meets extracting thread cutting requirements and prolongs the life of dies and chasers. Will not stain brass or copper. USDA listed. Contains no nitrosamines.



Quart **40-115** **\$27.05**
Gallon **40-120** **\$62.92**

Lubricant Stick Wax

- Safe and effective lubricant for grinding wheels, sanding belts and saw blades
- Eliminates heat build up and belt loading
- Extends wheel life
- Provides smooth, cool cutting
- Reduces loading, stops binding, and prevents burring



15 oz. Stick
15-SK
\$12.60

Cutting Oil

DARK - For high speed machine threading requirements. A blend of high quality mineral oils with sulfur-lard base. Protects valuable dies and chasers. Enables operator to cut precision threads. USDA listed. Contains no nitrosamines.



Quart **40-215** **\$27.05**
Gallon **40-220** **\$62.92**
5 Gallon **40-225** **\$306.94**

Rel-Saw Water Soluble Coolant

- Improves blade life
- Stable over a wide variety of water conditions
- Promotes cleaner-running machines compared to soluble oils
- Reduces machine wear
- Long emulsion life
- Contains rust and corrosion inhibitors



Gallon Bottle
01G-RS
\$36.45

Cutting Oil (water based)

This non-flammable, water-based cutting oil improves metal cutting operations and increases efficiencies in machining operations.

- Recommended for use on all metals including stainless steel and soft metals such as aluminum, brass, and copper.



16 oz. Aerosol
890-A
\$5.87

All-Purpose Paste Lubricant

- Great for tapping, drilling, reaming, etc.
- Contains EP agents for anti-weld protection
- Retains its lubrication properties longer than liquid products
- Convenient manual or automatic application to cutting surfaces
- Increases production rates and extends tool life
- Reduces heat and improves surface finishes
- Has excellent wetting properties



8 oz. Jar
08Z-NRTP
\$12.60

Hydraulic & Jack Oil

A medium weight hydraulic oil blended of a high quality paraffinic base oil with anti-rust, anti-oxidation, anti-foam, anti-wear, and seal swell additives. It is a 20W, non-detergent oil.

Applications Hydraulic systems and fluid drive units. May be added to existing fluids. Not for use in hydraulic brakes.



Quart
SL2552
\$13.21

NEW RAPID TAP - All Metal Cutting Fluid

- Super-fine machined finish in operation after operation.
- Anti-mist protection for a healthier work environment.
- Contains no 1,1,1-trichloroethane or other ozone-depleting chemicals.
- Greatly extended tool life
- No special labeling or reporting.



4 oz. **04Z-NRT** **\$3.75**
16 oz. **PNT-NRT** **\$12.00**