#### Super Glue

Instantly bonds glass, metal, plastics and rubber. Bonds close fitting parts in seconds. Works on aluminum, copper, brass, steel, vinyl, PVC, polyester, nylon, fiberglass and wood. Holding strength to 5000 psi.

## **Dynatex**

3 g. Bottle 49403 \$1.96



Battery Terminal Protector

Dynatex Battery Terminal Protector prolongs battery life by protecting battery terminals and connectors against moisture and corrosions. It also resists heat aging.

- · Prevents terminal corrosion
- · Prevents battery drain
- · Increases battery life
- · Improves electrical flow

**Dynatex** 

12 oz.

Aerosol Can 49678 \$6.84

Clear RTV Silicone Adhesive/Sealant
Provides transparent, watertight silicone rubber seal for
a wide range of applications. Bonds and seals metal,
plastics, glass, fabric, vinyl, wood and rubber. Use on
windshields, sunroofs, tail lights, interior panels,
fire walls and dashboards.

Cures at room temperature.

# Dynatex

3 oz. Tube 49204 \$5.32 11 oz. Cartridge 49294 \$16.56 Bolt Locker Blue Medium Strength Fills gaps up to .006 inches. Apply prior to assembly. Eliminates need for stocking lock nuts and lock washers. Can be removed without special tools.



6 ml. Bottle 49441 \$6.94 24 ml. Bottle 49442 \$18.64



Blue RTV Silicone Gasket Maker-L/V Replaces most cut gaskets. Resist cracking, shrinking and migration caused by thermal expansion. Cures tough and flexible. Temperature resistant up to 500° F. Resist oil, water, anti-freeze and transmission fluid. For valve covers, oil pans, transmission pans, rear-end housings, timing chain covers, thermostat housings, water pumps and oil pump flanges. Provides exceptional leak control and torque retention.

Dynatex

11 oz. Cartridge 49293 \$16.58

Bolt Locker Red High Strength Locks and seals metal threaded assemblies where high strength is required. Fills gaps up to .008 inches. Apply prior to assembly. Protects against thread corrosion.



6 ml. Bottle 49451 \$6.94 24 ml. Bottle 49452 \$18.64



## Cold Weld Compound

A 15-minute, two-part adhesive and filler system that eliminates the need for welding or brazing. Once cured, it can be drilled, sanded, painted or filed. Resists most automotive, shop and cleaning fluids. Withstands temperatures to 300°F intermittent. Over 3,000 PSI shear strength on steel.

## **Permatex**

(2) 1 oz. Tubes, Resin and Hardener 14600-L \$8,22



Bolt Locker Green Medium Strength Locks and seals metal threads after assembly and adjustments are complete. Fills gaps up to .005 inches. Migrates into pre-assembled threaded parts. Secures adjustments and set screws.

#### **Dynatex**

6 ml. Bottle 49461 \$6.42 24 ml. Bottle 49462 \$17.24



