

Rockite

- Expansion cement
- Stronger than concrete in one hour
- Dries in 15 minutes
- For anchoring and patching



DESCRIPTION	ITEM #	PRICE
5 lbs. Box	10006-H	\$8.73
25 lbs. Box	10025-H	29.72
50 lbs. Pail	10051-H	56.72

Stainless Steel Cutting Oil

- Cools threads and pipe during operation.
- For Stainless Steel and low quality pipe
- Reduces threading torque.
- Improves thread quality.
- Speeds metal removal.

RIDGID

NEW



We use this for threading stainless steel pipe.

1 Gallon
74012
\$50.65

Welding Anti-Spatter

A vegetable based formula that provides a protective film coating to aid in the removal of weld spatter and keeps welding tips and nozzles clean.

- Light yellow, tacky film visually confirms coverage
- Eliminates grinding and chiseling
- Quick and easy clean up
- Prevents spatter from adhering to surrounding metal surfaces

16 oz. Aerosol

887-A
\$5.99

CROWN



Air Spray Gun

The 1 quart spray gun is excellent for most types of spraying. It has a nonstick teflon lined dripless cup and hanger hook on the top of the gun.



31223
\$24.95

Air Tool Lubricant #10 Weight

A specially formulated High Grade Lubricant prolongs the service life of Air Tools, Cylinders and Accessories while permitting maximum performance. Prohibits rust and removes moisture as it lubricates. It is non-corrosive, non-reactive and doesn't decompose. This compound is superior in performance to ordinary lubricates

DIXON



SIZE	ITEM #	PRICE
1 Pint	DATL-016	\$15.65
1 Gallon	DATL-128	53.87

Steel Renew S.S. Coating

Provides optimum resistance to weather, abrasion, and corrosion. Protects metal, chrome, ceramic, and copper surfaces.

- Contains 100% 316L stainless steel pigment
- Performs at temperatures up to 350°F
- Creates a hard finish ideal for metal parts, equipment, and machinery
- Resistant to UV, chemicals, oils, alkalis, food acids, and water

AERVOE

NEW



13 oz. Aerosol
145-A \$11.74

REL-AIR™ - Compressor Oil

For use with: Sliding Vane, Screw, Centrifugal, and Reciprocating air compressors.

- Reduces sludge, varnish, and deposit formation
- Forms a protective coating on bearings, piston rings, valves, spindles, and cylinder walls
- Eliminates chatter
- Minimizes rust or corrosion
- Reduces compressor start-up wear

RELTON

Quart QRT-RA \$8.10
Gallon 01G-RA \$24.30



Rebar Green Epoxy Coating

A high-performance, single system epoxy coating that is specially designed for touch-up or as an initial coating of rebar.

- Prevents rust and the resulting stains when applied to rebar before setting in concrete
- Meets ASTM D3963 specifications
- Performs at temperatures up to 300°F
- Very good resistance to corrosion, chemicals, gasoline, and abrasion

AERVOE

NEW



12 oz. Aerosol
156-A
\$8.26