



REGULAR LAY ROPE
 Regular lay rope is the most standard, and accepted for a wide range of applications. The direction of the individual wires is opposite to the direction of the strands. Because of this, the rope is less likely to untwist, and therefore is easier to handle than lang lay rope. This rope is also less subject to crushing.



COATED WIRE ROPE
 If the full strength of the bare cable is required, plastic must be stripped from cable, with the fittings attached in direct contact with the cable.

WIRE ROPE							
DIAMETER	STRAND TYPE	TYPE	WORKING LOAD	LENGTH PER REEL	ITEM #	PRICE PER FOOT	PRICE FULL REEL
1/16"	7 x 7	GAC	80 lbs.	1000'	116WRG	.08	\$50.00
3/32"	7 x 7	GAC	153 lbs.	1000'	332WRG	.10	60.00
1/8"	7 x 19	GAC	333 lbs.	500'	18WRG	.21	65.00
3/16"	7 x 19	GAC	700 lbs.	500'	316WRG	.34	105.00
1/4"	7 x 19	GAC	1,166 lbs.	500'	14WRG	.51	160.00
5/16"	7 x 19	GAC	1,633 lbs.	500'	516WRG	.72	225.00
3/8"	7 x 19	GAC	2,400 lbs.	500'	38WRG	.96	300.00
7/16"	6 x 25	IWRC	2,960 lbs.	500'	716WRI	1.28	400.00
1/2"	6 x 25	IWRC	3,830 lbs.	500'	12WRI	1.80	563.00
5/8"	6 x 25	IWRC	4,830 lbs.	500'	58WRI	2.72	850.00
PLASTIC COATED WIRE ROPE							
1/8" x 3/16"	7 x 19	GAC	333 lbs.	500'	18WRC	.28	90.00
3/16" x 1/4"	7 x 19	GAC	700 lbs.	500'	316WRC	.44	140.00
1/4" x 5/16"	7 x 19	GAC	1,166 lbs.	500'	14WRC	.60	190.00
STAINLESS STEEL WIRE ROPE							
1/8"	7 x 19	SSC	290 lbs.	500'	18WRSS	.68	215.00
3/16"	7 x 19	SSC	616 lbs.	500'	316WRSS	1.28	400.00
GAC = Galvanized Aircraft Cable							
IWRC = Independant Wire Rope Center							
SSC = Stainless Steel Cable							

Stainless Steel Cable Clamps

• Standard Material:

Base is cast stainlee steel with stainless steel hex nuts




CABLE SIZE	TORQUE FOOT LBS.	MIN. CLAMPS REQUIRES	ITEM #	PRICE
1/8"	5	2	18SSCC	\$2.07
3/16"	8	2	316SSCC	2.64

Wire Gripper - Cam Action

A must-have for fence builders, farmers and ranchers! Use to assist in stretching barbwire, smooth wire and small cable. Safe, easy to use.



48590
 \$19.95



NICOPRESS				
WIRE ROPE DIAMETER	ITEM #	PRICE 1 - 10	PRICE 11 - 50	PRICE 51 & UP
1/16"	116NPS	.16	.14	.12
3/32"	332NPS	.31	.27	.23
1/8"	18NPS	.66	.57	.49
3/16"	316NPS	2.08	1.82	1.56
1/4"	14NPS	3.44	3.01	2.58
5/16"	516NPS	5.12	4.48	3.84

NYLON MASON LINE

Tough, durable 100% nylon mason line lasts many times longer than cotton. It is abrasion resistant, rot resistant, and can be stored while wet without damage to the fiber. This line is resistant to oil grease, gasoline, and most chemicals. In addition to its primary use, mason line is useful for fishing line, chalk line, and duck decoy anchor line.



NYLON MASON TWINE					
SIZE	WEIGHT PER ROLL	TYPE	LENGTH PER REEL	ITEM NUMBER	PRICE FULL ROLL
#18	8 oz.	Yellow	525'	188YNT	\$5.84
#18	16 oz.	Yellow	1100'	1816YNT	10.50
SISAL BINDER TWINE					
	5 lbs.	1-Ply	550'	SBT	9.40