

WHITE NYLON TWISTED

Strongest rope available, over twice as strong as manila. Yarns are heat set to enable the finished ropes to remain flexible when used in water. Excellent energy absorption, with greater elasticity than any other rope, but caution must be exercised due to high recoil at breakpoint. Flexible, high abrasion resistance, can be stored wet, resists most weak acids and alkali solutions and will not rot. Excellent for towing, pleasure boating and many commercial fishing applications.

DIAMETER	PRICE 0 - 99'	PRICE 100' - 199'	PRICE 200' - 599'	PRICE FULL REEL	ITEM NUMBER	WORKING LOAD	LENGTH PER REEL
1/8"	.11	.09	.07	\$60.00	18WNR	-----	1000'
3/16"	.15	.12	.09	42.00	316WNR	75 lbs.	600'
1/4"	.22	.18	.14	66.00	14WNR	124 lbs.	600'
5/16"	.35	.28	.22	102.00	516WNR	192 lbs.	600'
3/8"	.50	.40	.31	150.00	38WNR	278 lbs.	600'
1/2"	.87	.71	.55	264.00	12WNR	525 lbs.	600'

MANILA

The best natural fiber rope. Good abrasion resistance and low stretch but less than half the strength of synthetics. Attacked by most chemicals, Manila absorbs water and is subject to mildew and rot.

DIAMETER	PRICE 0 - 99'	PRICE 100' - 199'	PRICE 200' - 599'	PRICE FULL REEL	ITEM NUMBER	WORKING LOAD	LENGTH PER REEL
3/8"	.15	.12	.10	\$48.00	38MR	122 lbs.	600'
1/2"	.43	.35	.27	132.00	12MR	264 lbs.	600'
5/8"	.77	.62	.48	228.00	58MR	496 lbs.	600'
3/4"	.93	.76	.58	282.00	34MR	695 lbs.	600'
1"	1.54	1.25	.96	462.00	1MR	1,160 lbs.	600'

YELLOW POLYPROPYLENE

The most popular general purpose synthetic rope. Polypropylene has the best resistance to flow of electricity and is widely used in the electric utility industry. Float with high resistance to mildew and marine growth, and good resistance to most chemicals. Due to its relatively low melting point (330°F) it is not recommended on capstans or bits where heat from friction could cause melting or fusing. Knots well, handles easily, good flexibility in cold temperatures, with wide usage in marine, farm, commercial fishing and utility industries. Polypropylene has added UV stabilization to resist sunlight degradation.

DIAMETER	PRICE 0 - 99'	PRICE 100' - 199'	PRICE 200' - 599'	PRICE FULL REEL	ITEM NUMBER	WORKING LOAD	LENGTH PER REEL
3/16"	.07	.06	.05	\$48.00	316YPPR	72 lbs.	1,200'
1/4"	.10	.08	.06	30.00	14YPPR	113 lbs.	600'
5/16"	.14	.12	.09	42.00	516YPPR	171 lbs.	600'
3/8"	.20	.16	.13	60.00	38YPPR	244 lbs.	600'
1/2"	.35	.28	.22	102.00	12YPPR	420 lbs.	600'
5/8"	.57	.46	.36	174.00	58YPPR	700 lbs.	600'

BLACK / ORANGE POLYPROPYLENE (CTR)

All Polypro Truck Ropes conform to California State Highway Patrol requirements.

DIAMETER	PRICE 0 - 99'	PRICE 100' - 199'	PRICE 200' - 599'	PRICE FULL REEL	ITEM NUMBER	WORKING LOAD	LENGTH PER REEL
3/8"	.20	.16	.13	\$60.00	38CTR	244 lbs.	600'
1/2"	.35	.28	.22	102.00	12CTR	420 lbs.	600'
5/8"	.57	.46	.36	174.00	58CTR	700 lbs.	600'
3/4"	.73	.60	.46	222.00	34CTR	1,090 lbs.	600'
1"	1.26	1.03	.79	378.00	1CTR	1,800 lbs.	600'