

Anchor Shackles

- Standard Material: Shackle bodies are drop-forged carbon steel
- Standard Finish: Galvanized to meet ASTM A-153 specifications
- Design factor: 5 to 1



Campbell®

| BODY SIZE | WORKING LOAD LIMIT | PIN DIA. | INSIDE WIDTH | ITEM # | PRICE |
|-----------|--------------------|----------|--------------|----------|--------|
| 3/16" | 1/3 ton | 1/4" | 19/32" | 541-0335 | \$5.58 |
| 1/4" | 1/2 ton | 5/16" | 25/32" | 541-0435 | 5.52 |
| 5/16" | 3/4 ton | 3/8" | 27/32" | 541-0535 | 6.22 |
| 3/8" | 1 ton | 7/16" | 31/32" | 541-0635 | 7.60 |
| 1/2" | 2 ton | 5/8" | 1-1/4" | 541-0835 | 10.40 |
| 5/8" | 3-1/4 ton | 3/4" | 1-9/16" | 541-1035 | 17.88 |
| 3/4" | 4-3/4 ton | 7/8" | 1-13/16" | 541-1235 | 27.10 |
| 7/8" | 6-1/2 ton | 1" | 2-1/16" | 541-1435 | 36.38 |
| 1" | 8-1/2 ton | 1-1/8" | 2-1/2" | 541-1635 | 49.08 |
| 1-1/4" | 12 ton | 1-3/8" | 3-1/4" | 541-2035 | 107.00 |
| 1-1/2" | 17 ton | 1-5/8" | 3-7/8" | 541-2435 | 175.28 |

Malleable Cable Clamps

- Standard Material: Base is cast malleable iron with regular hex nuts



Campbell®

| CABLE SIZE | TORQUE FOOT LBS. | MIN. CLAMPS REQUIRES | ITEM # | PRICE |
|------------|------------------|----------------------|-----------|-------|
| 1/8" | 5 | 2 | T767-0419 | .62 |
| 3/16" | 8 | 2 | T767-0429 | .80 |
| 1/4" | 15 | 2 | T767-0439 | 1.04 |
| 5/16" | 30 | 2 | T767-0449 | 1.06 |
| 3/8" | 45 | 2 | T767-0459 | 1.42 |
| 1/2" | 65 | 2 | T767-0479 | 2.12 |

Drop Forged Cable Clamps

- Standard Material: Base is drop-forged carbon steel, with heavy hex nuts
- Standard Finish: Galvanized to meet ASTM A-153 specifications



Campbell®

| CABLE SIZE | TORQUE FOOT LBS. | MIN. CLAMPS REQUIRES | ITEM # | PRICE |
|------------|------------------|----------------------|----------|--------|
| 1/8" | 5 | 2 | 699-0234 | \$3.44 |
| 3/16" | 8 | 2 | 699-0334 | 3.56 |
| 1/4" | 15 | 2 | 699-0434 | 4.48 |
| 5/16" | 30 | 2 | 699-0534 | 4.66 |
| 3/8" | 45 | 2 | 699-0634 | 5.30 |
| 7/16" | 65 | 2 | 699-0734 | 8.10 |
| 1/2" | 65 | 3 | 699-0834 | 8.10 |
| 5/8" | 95 | 3 | 699-1034 | 10.26 |
| 3/4" | 130 | 4 | 699-1234 | 12.98 |
| 1" | 225 | 5 | 699-1634 | 21.52 |

Jaw & Eye Swivels

- Standard Material: Drop-forged carbon steel
- Standard Finish: Galvanized to meet ASTM A-153 specifications
- Design Factor: 5 to 1



Campbell®

| SIZE | OVERALL LENGTH | PIN DIA. | WORKING LOAD LIMIT | ITEM # | PRICE |
|-------|----------------|----------|--------------------|----------|---------|
| 1/4" | 3-5/32" | 1/4" | 850 lbs. | 364-0435 | \$23.76 |
| 5/16" | 3-3/4" | 5/16" | 1250 lbs. | 364-0535 | 25.22 |
| 3/8" | 4-5/8" | 3/8" | 2250 lbs. | 364-0635 | 27.72 |
| 1/2" | 6-1/8" | 1/2" | 3600 lbs. | 364-0835 | 38.32 |
| 5/8" | 7-3/8" | 5/8" | 5200 lbs. | 364-1035 | 62.28 |
| 3/4" | 8" | 3/4" | 7200 lbs. | 364-1235 | 85.06 |
| 1" | 11-7/16" | 1-1/8" | 12,500 lbs. | 364-1635 | 191.08 |

Eye & Eye Swivel

- Standard Material: Drop-forged carbon steel
- Standard Finish: Galvanized to meet ASTM A-153 specifications
- Design Factor: 5 to 1



Campbell®

| SIZE | OVERALL LENGTH | WORKING LOAD LIMIT | ITEM # | PRICE |
|-------|----------------|--------------------|----------|---------|
| 1/4" | 3-3/8" | 850 lbs. | 363-0435 | \$18.94 |
| 5/16" | 4-1/8" | 1250 lbs. | 363-0535 | 20.46 |
| 3/8" | 5" | 2250 lbs. | 363-0635 | 24.50 |
| 1/2" | 6-3/4" | 3600 lbs. | 363-0835 | 32.04 |
| 5/8" | 8" | 5200 lbs. | 363-1035 | 47.98 |
| 3/4" | 8-3/4" | 7200 lbs. | 363-1235 | 62.98 |
| 1" | 11-3/4" | 12,500 lbs. | 363-1635 | 128.32 |

Galvanized Eye Bolts

- Standard Material: Drop-forged carbon steel
- Standard Finish: Galvanized to meet ASTM A-153 specifications
- Working load limits apply only to eyebolts in lifting or pulling applications



| BOLT SIZE | LENGTH | EYE DIA. | WORKING LOAD LIMIT | ITEM # | PRICE |
|-----------|--------|----------|--------------------|----------|--------|
| 1/4" | 2" | 1/2" | 500 lbs. | 80057-C | \$5.26 |
| 1/4" | 4" | 1/2" | 500 lbs. | 80118-C | 6.09 |
| 5/16" | 2-1/4" | 5/8" | 800 lbs. | 80224-C | 6.29 |
| 5/16" | 4-1/4" | 5/8" | 800 lbs. | 80286-C | 6.80 |
| 3/8" | 2-1/2" | 3/4" | 1200 lbs. | 80392-C | 6.86 |
| 3/8" | 4-1/4" | 3/4" | 1200 lbs. | 80453-C | 8.51 |
| 3/8" | 6" | 3/4" | 1200 lbs. | 80514-C | 9.53 |
| 1/2" | 6" | 1" | 2200 lbs. | 80682-C | 11.59 |
| 1/2" | 8" | 1" | 2200 lbs. | 80712-C | 16.83 |
| 1/2" | 10" | 1" | 2200 lbs. | 80743-C | 20.55 |
| 5/8" | 4" | 1-1/4" | 3500 lbs. | 80828-C | 14.39 |
| 5/8" | 6" | 1-1/4" | 3500 lbs. | 80859-C | 17.58 |
| 5/8" | 8" | 1-1/4" | 3500 lbs. | 80880-C | 26.62 |
| 3/4" | 4-1/2" | 1-1/2" | 5200 lbs. | 801085-C | 21.21 |
| 3/4" | 6" | 1-1/2" | 5200 lbs. | 801115-C | 24.11 |
| 1" | 6" | 2" | 10,000 lbs. | 801511-C | 49.52 |