

SPECIALTY FASTENERS

1514-

INTERNAL RETAINING RINGS

A	3/4	.45¢
B	7/8	.55
C	1	.63
D	1-1/8	.71
E	1-1/4	.81
F	1-1/2	.99
G	1-3/4	1.36



1514-

EXTERNAL RETAINING RINGS

H	7/8	.71¢
I	1	.81
J	1-1/8	.91
K	1-1/4	1.09
L	1-1/2	1.26
M	1-3/4	1.54



1515-

EXTERNAL RINGS

A	1/4	.23¢
B	5/16	.23
C	3/8	.23
D	7/16	.23
E	1/2	.23
F	9/16	.32
G	5/8	.32
H	3/4	.32



1515-

"E" RINGS

I	3/16	.13¢
J	7/32	.13
K	1/4	.19
L	5/16	.19
M	3/8	.19
N	7/16	.23
O	1/2	.23
P	5/8	.28



0933-

SHORT ARM HEX WRENCHES

A	1/16	.50¢
B	5/64	.50
C	3/32	.50
D	1/8	.50
E	5/32	.60
F	3/16	.60
G	7/32	1.50
H	1/4	1.50
I	5/16	1.89



1532-

ROLLER LINKS

A	#35	\$1.44
B	#40	1.54
C	#41	1.44
D	#43 (65)	1.09
E	#50	2.07



1532-

OFFSET LINKS

F	#35	\$2.43
G	#40	2.80
H	#41	2.43
I	#43 (65)	2.43
J	#50	3.34



1532-

CONNECTING LINKS

K	#35	\$1.54
L	#40	1.64
M	#41	1.44
N	#43 (65)	1.17
O	#50	2.16



0813-

AUTOMOTIVE STUDS HEAT TREATED (SAE)

A	1/4-20 & 28 x 1-1/2	\$1.80
B	1/4-20 & 28 x 2	1.80
C	5/16-18 & 24 x 1-1/2	1.80
D	5/16-18 & 24 x 2	1.80
E	1/4-20 & 28 x 2-1/2	1.80
F	5/16-18 & 24 x 2-1/2	2.29
G	3/8-16 & 24 x 1-1/2	2.29
H	3/8-16 & 16 x 2	2.29
I	3/8-16 & 24 x 2	2.29
J	3/8-16 & 24 x 2-3/4	2.29
K	3/8-16 & 16 x 3	2.29
L	7/16-14 & 14 x 2-1/2	2.55



0814-

AUTOMOTIVE STUDS HEAT TREATED (Metric)

A	M6 x 23mm	\$3.09
B	M6 x 31mm	3.09
C	M8 & M6 x 23mm	3.09
D	M8 & M6 x 31mm	3.09
E	M8 x 31mm	3.09
F	M8 x 38mm	3.09
G	M8 x 46mm	3.09
H	M8 x 50mm	3.09
I	M8 x 62mm	3.09
J	M10 x 48mm	3.09
K	M10 & M8 x 38mm	3.09



1530-

AXLE BOLTS with NUTS

A	3/8-16 STAR NUT	.45¢
B	1/2 x 1-5/16	1.80
C	1/2 x 1-3/8	1.72
D	1/2 x 1-7/16	1.40
E	1/2 x 1-1/2	2.55
F	1/2 x 1-5/8	1.99
G	1/2 x 1-3/4	2.07
H	1/2 x 1-7/8	2.15



1533-

GREASE FITTINGS (SAE)

A	1/4-28 S STRAIGHT	.81¢
B	1/4-28 L STRAIGHT	.99
C	1/4-28 45°	1.80
D	1/4-28 90°	1.99
E	1/8 NPT STRAIGHT	1.26
F	1/8 NPT 30°	2.07
G	1/8 NPT 45°	2.07
H	1/8 NPT 65°	2.07
I	1/8 NPT 90°	2.16



1534-

GREASE FITTINGS (Metric)

A	6mm x 1mm STR.	.81¢
B	6mm x 1mm 45°	1.72
C	6mm x 1mm 45°	1.72
D	8mm x 1mm STR.	.99
E	8mm x 1mm 45°	1.99
F	8mm x 1mm 90°	1.99
G	10mm x 1mm STR.	1.26
H	10mm x 1mm 45°	1.99
I	10mm x 1mm 90°	1.99

